

FORMULA X[®] UHP ULTRA HIGH PERFORMANCE STRIPPER

Powerful, ultra-high performance, non-ammoniated formula cuts through heavy build-up and hard to remove water-based seals in record time.

FEATURES

- Cool water formula evaporates more slowly than hot water formulas
- Quick acting – requires as little as 5-10 minutes contact time
- Labor savings – removes most sealers in one pass
- Economical – works effectively at high dilution ratios
- Low foaming
- Pleasant citrus fragrance



RECOMMENDED FLOOR SURFACES

All resilient tile flooring, linoleum and most types of terrazzo, marble and quarry tile.

Not recommended for asphalt or rubber tile flooring.

NOTE: Test floor for color fastness in an inconspicuous area.

PRODUCT DATA

Description:	Non-ammoniated, ultra high performance stripper
Appearance:	Clear liquid
Fragrance:	Citrus
Viscosity (Brookfield):	<10 centipoise @ 68°F (20°C)
Flash Point:	150°F, (66°C) ASTM method D56
Shelf Life:	2 years, ASTM D1791-93 (1998)
Density:	8.3 lb per gal @ 68°F 1.00 kg per liter @ 20°C
Freeze/Thaw:	Passes 3 cycles ASTM D3209-93 (1998)

PRECAUTIONS

Keep out of reach of children. Keep container sealed when not in use. Keep from freezing. Combustible. Gloves and safety glasses recommended. Floor may become very slippery. Wear appropriate non-slip safety shoes. This product should not be used in contact with asphalt or rubber tile flooring, wood, or painted surfaces. Please read the Material Data Sheet before handling this product.

ORDERING INFORMATION

Product #503FS:	2 x 2.50 gallon per case (2 x 9.5 liter)
Product #503MP:	4 x 1.06 gallon per case (4 x 4 liter)

DIRECTIONS FOR USE

1. Mix Formula X UHP Floor Stripper in mop bucket or automatic scrubber according to the following dilution ratios:

For sealer and coating removal:

1:4 32 US oz per gal cold water (1,25 liters per 5 liters cold water)

For finish removal only:

1:8 16 US oz per gal cold water (0,62 liter per 5 liters cold water)

For use on linoleum:

1:16 8 US oz per gal cold water (0,31 liter per 5 liters cold water)

2. Apply solution liberally to floor and allow to soak for 5-10 minutes. Do not let floor dry - keep floor wet using additional solution as required.
3. Scrub floor with recommended automatic scrubber or Amano Pioneer Eclipse stripping machine with Amano Pioneer Eclipse pads or brushes.
4. Pick up dirty solution with automatic scrubber or wet vac.
5. Use a clean mop or automatic scrubber to rinse floor twice with an Amano Pioneer Eclipse neutral cleaner following label directions.
6. Rinse floor again with clean cold water. Allow to dry thoroughly before applying sealer or coating.

NOTE: Works most effectively in cold water.

FORMULA X UHP ULTRA HIGH PERFORMANCE STRIPPER

LAST REVISION DATE: 03/11/08
MANUFACTURER: Amano Pioneer Eclipse® Corp.
 Sparta, NC 28675 Phone: 1-336-372-8080
FOR CHEMICAL EMERGENCY: Spill, Leak, Fire,
 Exposure or Accident **CALL CHEMTREC - Day**
or Night 1-800-424-9300 Toll Free in the
 Continental US **483-7616** in DISTRICT OF
 COLUMBIA. For calls originating outside the US:
 Call Collect **1-202-483-7616** Washington, DC.

SECTION I: GENERAL INFORMATION

PRODUCT NAME: Formula X® UHP Ultra High Performance Stripper
PRODUCT #: 503
PRODUCT TYPE: Non-ammoniated, ultra high performance stripper
PRECAUTIONS: Corrosive. Do not get in eyes, on skin or clothing. Keep container sealed when not in use. Keep out of reach of children.
HEALTH: 2
FLAMMABILITY: 2
REACTIVITY: 0
NFPA HAZARD RATINGS

4-EXTREME	3-HIGH	2-MODERATE
1-SLIGHT	0-INSIGNIFICANT	



SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT: Monoethanolamine
CAS#: 141-43-5
%: 5-10
OSHA PEL: 3 ppm (TWA)
ACGIH TLV: 6 ppm (STEL) 3 ppm (TWA)
LD₅₀ SPECIES & ROUTE: 1.2 g/kg rat, oral

INGREDIENT: *Ethylene Glycol Butyl Ether
CAS#: 111-76-2
%: 20-25
OSHA PEL: 50 ppm (skin) (TWA)
ACGIH TLV: 20 ppm (TWA)
LD₅₀ SPECIES & ROUTE: 0.5 g/kg rat, oral

* This chemical is subject to the reporting requirements of Section 313 of SARA Title III.

N/E = Not Established, N/L = Not Listed
 N/A = Not Applicable

SECTION III: PHYSICAL/CHEMICAL DATA

APPEARANCE: Clear liquid
pH: 12.2 ± 0.5
BOILING POINT: 100°C / 212°F
EVAPORATION RATE: Less than water
FREEZING POINT: 0°C / 32°F
VAPOR DENSITY: Greater than air
VOLATILE BY WEIGHT: 92-95%
VAPOR PRESSURE: Less than water
DENSITY: 8.3 lb per gal @ 68°F
 1.00 kg per liter @ 20°C
SOLUBILITY IN WATER: Miscible

SECTION IV: FIRE AND EXPLOSION DATA

FLASH POINT: 150°F, 66°C ASTM method D56
EXPLOSIVE LIMITS:
 LOWER: N/E UPPER: N/E
EXTINGUISHING MEDIA: Water spray, CO₂, dry chemical, alcohol-type or universal type foams
SPECIAL FIRE FIGHTING PROCEDURES: Do not spray a solid stream of water or foam directly into hot liquid. This may cause frothing. Firefighters should wear NIOSH approved breathing apparatus.
HAZARDOUS COMBUSTIBLE PRODUCTS: N/A
UNUSUAL FIRE AND EXPLOSION HAZARDS: Materials can splatter above 100°C / 212°F.

SECTION V: REACTIVITY DATA

STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur.
INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids and strong oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide and nitrogen oxides
REACTIVITY CONDITIONS: None

SECTION VI: HEALTH HAZARD DATA

EYES: May cause severe burns or possible corneal damage. For eye contact, flush with a large amount of water for at least 15 minutes. See a physician immediately.
SKIN: Irritation, reddening or possible damage upon repeated or prolonged contact. For skin contact, wash affected areas with soap and water. Seek medical attention if irritation persists.
INHALATION: Vapor or mist can cause headache, nausea and irritation of the eyes, nose, throat and lungs. For overexposure, move subject to fresh air. Seek medical attention if symptoms persist.
INGESTION: May cause nausea, abdominal discomfort, vomiting, diarrhea. If ingested, give two glasses of water or milk and do not induce vomiting. Remove by endotracheal intervention. Seek medical attention immediately.
CHRONIC EFFECTS AND MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: Main hazard is due to product's severe irritant properties. Treatment should be directed at the control of symptoms and the clinical condition of the patient.
CARCINOGEN: Non-carcinogenic
REPRODUCTIVE EFFECTS: N/E
TERATOGENICITY: N/E
MUTAGENICITY: N/E
THRESHOLD LIMIT VALUE: See Section II.

SECTION VII: SPILL, LEAK & DISPOSAL PROCEDURES

SMALL SPILLS: Absorb spill with inert material (e.g. sand, earth) and dispose of as waste material in accordance with local, state and federal regulations. Neutralize residue with vinegar, mild acid or large amount of water.

LARGE SPILLS: Keep spectators away. Floors may be slippery; use care to avoid falling. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep spills and cleaning runoff out of sewers and open bodies of water.
WASTE DISPOSAL: Dispose of as waste material in accordance with local, state, and federal regulations.

SECTION VIII: SPECIAL PROTECTION

EYE PROTECTION: Chemical splash goggles (ANSI Z87.1-1989 or approved equivalent)
RESPIRATORY PROTECTION: None required when permissible airborne concentrations are not exceeded. In emergency, use approved positive pressure self-contained breathing device.
VENTILATION: Mechanical local exhaust ventilation at point of contamination release
OTHER PROTECTIVE EQUIPMENT: As required by employer code. Rubber boots and chemical resistant gloves recommended.

SECTION IX: SPECIAL PRECAUTIONS

HANDLING AND STORAGE: Storage temperature (MAX. 60°C / 140°F) (MIN. 1°C / 34°F)
OTHER PRECAUTIONS: Keep from freezing.

SECTION X: ADDITIONAL INFORMATION

Neither this data sheet nor any statement contained herein grants or extends any license, expressed or implied, in connection with patents issued or pending which may be the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer based on its own studies and the work of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) or the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information.

This MSDS has been provided to you in accordance with the OSHA HAZARD COMMUNICATION STANDARD (29CFR1910.1200).

***IMPORTANT SAFETY INFORMATION
 DO NOT DISCARD***
 PLEASE ROUTE TO COMPANY SAFETY OFFICER

